

# Essolube XT 5 15W-40

## Super Premium Diesel Engine Oil

### Product Description

Essolube XT 5 15W-40 is a super premium diesel engine oil that provides outstanding protection in the most severe diesel engine applications. It is formulated with highly refined base stocks and advanced additives for maximum engine protection and extended oil drain intervals. Essolube XT 5 15W-40 is highly recommended for use in all super high performance diesel engines including today's low emission engines.

### Features & Benefits

Today's low emission engines place increasing demands on engine lubricants. The quality and versatility built into Essolube XT 5 15W-40 delivers exceptional reliability and performance in current diesel engines as well as older models. The key benefits include:

- Excellent oxidation stability that reduces engine deposits, sludge build up, and viscosity increase
- Effective TBN reserves that enable extended drain intervals
- Highly effective soot dispersion enabling outstanding wear control
- Balanced detergency that improves engine cleanliness
- Excellent anti-wear and anti-scuff properties that extend engine life and reduce maintenance costs

### Applications

- Naturally aspirated and turbo-charged diesel powered equipment from leading Japanese, European, and American manufacturers
- On-highway light and heavy-duty trucking including high speed/high load and pick-up/delivery
- Off-highway industries including: construction, mining, quarrying, and agriculture

### Specifications & Approvals

---

**Essolube XT 5 15W-40 meets or exceeds the following industry and builder specifications:**

---

API CH-4/CG-4/CF-4/CF/SJ

---

ACEA E5/E3/B4/B3

---

---

**Essolube XT 5 15W-40 has the following builder approvals:**

---

Daimler Chrysler MB 228.3

---

MAN M3275

---

Volvo VDS-3; VDS-2

---

Renault RVI RLD

---

Mack EO-M Plus

---

Cummins CES 20077/76/72/71

---

ExxonMobil Lubricants & Specialties

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union. All products may not be available locally. For more information, contact your local sales office or visit [www.exxonmobil.com](http://www.exxonmobil.com).

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.



**Essolube XT 5 15W-40 is recommended for use in applications requiring:**

Allison C-4

## Typical Properties

### Essolube XT 5 15W-40

SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	103
cSt @ 100°C	14.2
Viscosity Index, ASTM D 2270	140
Sulfated Ash, wt%, ASTM D 874	1.2
Total Base #, mg KOH/g, ASTM D 2896	10.6
Pour Point, °C, ASTM D 97	-33
Flash Point, °C, ASTM D 92	228
Density @ 15°C kg/l, ASTM D 4052	0.886

## Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Exxon (Esso) logotype, the Running Tigerr (and any other trademarks) including Essolube are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

#### ExxonMobil Lubricants & Specialties

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union. All products may not be available locally. For more information, contact your local sales office or visit [www.exxonmobil.com](http://www.exxonmobil.com).

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.

