

ESSO ATF LT 71141

Semi-synthetic Automatic Transmission Fluid

DESCRIPTION

ESSO ATF LT 71141 is a semi-synthetic product blended from carefully selected highly refined special base oils and modern additive technology to guarantee that it fulfils the severest ATF “fill for life” requirements of international automatic transmission manufacturers.

APPLICATION

Specifically designed for “fill for life” automatic transmission boxes.

PERFORMANCE

Meets or exceeds the following manufacturers’ approvals:-

Audi, VW, ZF and BMW

BENEFITS

- Long drain performance for use in automatic transmissions and power steering units.
- High performance semi-synthetic based oil suitable for operation over a wide temperature range.
- Meets the severest ATF “fill for life” requirements of major international transmission manufacturers.

Typical inspections		Method
Density @ 15 °C, kg/m ³	853	ASTM D 4052
Kinematic viscosity		
@ 40 °C, mm ² /sec (cSt)	37	ASTM D 445
@ 100 °C, mm ² /sec (cSt)	7.3	ASTM D 445
Brookfield viscosity		
@ -40 °C, mPa.s	18000	ASTM D 2983
Viscosity Index	168	ASTM D 2270
Flash point, °C	215	ASTM D 92
Pour point, °C	-54	ASTM D 97
Noack volatility, 200 °C, % mass	5	CEC-L-140-T.37
Foaming tendency/stability, ml		
Stage I	10/0	ASTM D 892
Stage II	30/0	ASTM D 892
Stage III	0/0	ASTM D 892
FZG Gear test,		
A/8.3/90 failure load stage	12	DIN 51354

HEALTH & SAFETY- This product is not classified as hazardous under the EC Dangerous Substances and Dangerous Preparations directives. Refer to ESSO Product Health and Safety Data Sheets for full information.

Esso Petroleum Company Ltd
Lubricants Department
Technical Enquiry Desk

Tel: 01372 222 553
Fax: 01372 222 368

Esso Petroleum Company Ltd
Head Office
ExxonMobil House, Ermyn Way
Leatherhead
Surrey KT22 8UX
01372 222 000

Esso Ireland Ltd
Head Office
Stillorgan
Blackrock
Co Dublin
01 2881661

IDS 20015
Issue 01/02