

Esso Ultron 5W-40

Super Premium Quality Synthetic Passenger Vehicle Engine Oil

Product Description

Esso Ultron 5W-40 is a super premium quality synthetic motor oil developed to provide the highest standard of lubricant reliability and protection for all types of automobile engines.

Features & Benefits

Esso Ultron 5W-40 is specially formulated with the highest quality synthetic baseoils and leading additive technology to provide the highest level of protection across a wide range of operating conditions. Key features and benefits include:

- Excellent thermal and oxidation stability to reduce engine deposits and sludge build up to keep engines running reliably
- Enhanced frictional properties to help save fuel
- Excellent low temperature capabilities for reliable cold weather starting allowing fast engine and electrical system protection
- High temperature fortified formulation provides reserve protection for the toughest driving conditions

Applications

Esso Ultron 5W-40 is specifically recommended for use in all types of vehicles, especially modern gasoline or diesel engines fitted with advanced computer controlled multi-valve fuel injection engines, turbochargers and other performance enhancement equipment. Esso Ultron 5W-40 is an excellent choice for all automobiles, light trucks and vans. It is the ideal choice anyone seeking the ultimate quality and dependable protection in a lubricant.

Specifications & Approvals

Esso Ultron 5W-40 meets or exceeds the following industry specifications:

API SL/SJ/CF

ACEA A3,B3,B4

Esso Ultron 5W-40 has the following OEM approvals:

BMW LONGLIFE OIL 98

Volkswagen 502 00 and 505 00

Mercedes Benz MB 229.3

Peugeot PSA E/D Level 3

Porsche

Opel GM-LL-B025

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.



Typical Properties

Filling	RN 4686 AAD
Esso Ultron 5W-40	
Viscosity, ASTM D 445	
cSt @ 40° C	84
cSt @ 100° C	14.2
Viscosity Index, ASTM D 2270	175
Sulfated Ash, wt%, ASTM D 874	1.02
HTHS Viscosity, mPa·s @ 150° C ASTM D4683	3.6
Pour Point, °C, ASTM D 97	-39
Flash Point, °C, ASTM D 92	220
Density @15° C kg/l, ASTM D 4052	0.855

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Exxon (Esso) logotype, the Running Tiger and Ultron are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.

