

# ESSO 2T SPECIAL

## High performance 2-stroke engine oil

### DESCRIPTION

ESSO 2T SPECIAL is a pre-diluted oil containing a special low smoke diluent.

It is based on specially selected base stocks and additives to ensure excellent performance that meets the latest motorcycle industry requirements.

### APPLICATION

ESSO 2T SPECIAL is suitable for use in a wide range of gasoline powered two-stroke equipment.

Particularly suitable for motorcycles where a reduced smoke lubricant is required, ESSO 2T SPECIAL gives excellent control of engine wear and exhaust port blocking.

May be used where lubrication is either by self-mix or oil injection.

### PERFORMANCE

Quality levels  
API TC  
JASO FC

### BENEFITS

- Reduced smoke
- Excellent engine cleanliness
- Prevents wear and spark plug fouling
- Prevents exhaust system blocking

Typical inspections		Method
Density @ 15 °C, kg/m <sup>3</sup>	870	ASTM D 4052
Kinematic viscosity		
@ 40 °C, mm <sup>2</sup> /sec (cSt)	46	ASTM D 445
@ 100 °C, mm <sup>2</sup> /sec (cSt)	7.5	ASTM D 445
Flash point, °C	70	ASTM D 92
Pour point, °C	-36	ASTM D 97
Sulphated ash, % mass	0.14	ASTM D 874

HEALTH & SAFETY- This product is not classified as hazardous under the EC Dangerous Substances and Dangerous Preparations directives. Refer to ESSO Product Health and Safety Data Sheets for full information.

**Esso Petroleum Company Ltd**  
Lubricants Department  
**Technical Enquiry Desk**

Tel: 01372 222 553  
Fax: 01372 222 368

**Esso Petroleum Company Ltd**  
Head Office  
ExxonMobil House, Ermyn Way  
Leatherhead  
Surrey KT22 8UX  
01372 222 000

**Esso Ireland Ltd**  
Head Office  
Stillorgan  
Blackrock  
Co Dublin  
01 2881661

**IDS 20017**  
Issue 01/02