

Esso 2T

Good Quality Two-Stroke Engine Oil

Product Description

Esso 2T is a two-stroke engine oil for use in motorcycles, snowmobiles and lean oil/fuel ratio chain saws.

Esso 2T is pre-diluted to ensure reliable efficient mixing when added to fuel.

Features & Benefits

Esso 2T combines highly quality mineral oils and a superior additive system providing good overall dependable protection. Key features and benefits include:

- Good wear protection for longer engine life
- Thermal stability and deposit control helps extend spark plug and valve life, reduces ring sticking, and piston tightening
- Good corrosion protection extends engine life
- Reduced pre-ignition improves fuel efficiency and extends piston life

Applications

Esso 2T is recommended for the lubrication of two-stroke engines used in motorcycles, snowmobiles and lean oil/fuel ratio chain saws, specifically for those requiring API TB and JASO FB oil quality.

Specifications & Approvals

Esso 2T meets or exceeds the following industry specifications:

Meets API TB	X
JASO FB	X

Typical Properties

Filling	RN 4602
Esso 2T	
Viscosity, ASTM D 445	
cSt @ 40° C	63
cSt @ 100° C	8.7
Viscosity Index, ASTM D 2270	110
Sulfated Ash, wt%, ASTM D 874	0.05
Pour Point, °C, ASTM D 97	-12
Flash Point, °C, ASTM D 92	132
Density @15° C kg/l, ASTM D 4052	0.878

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.





Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Exxon (Esso) logotype, the Running Tiger and 2T are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.

