



# Mobil Extra 2T

## Superior Performance Two-Stroke Engine Oil

### Product Description

Mobil Extra 2T is a superior performance; semi-synthetic, smokeless, two-stroke engine oil developed to meet for high performance motorcycles, snowmobiles and chain saws.

Mobil Extra 2T is pre-diluted to facilitate mixing when added to fuel.

### Features & Benefits

Mobil Extra 2T combines a blend of high quality mineral and synthesised high performance baseoils with an advanced additive system to provide excellent engine cleanliness and no-smoke exhaust performance. Key features and benefits include:

Features	Advantages and Potential Benefits
Excellent wear protection	Longer engine life
Good thermal and oxidation stability and deposit control	Cleaner engines resulting in extended spark plug and valve life, reduced ring sticking, piston tightening and prevention of pre-ignition problems
Excellent corrosion protection properties	Longer engine life
Smoke-free exhaust	Cleaner environment

### Applications

Mobil Extra 2T is specifically recommended for lubrication of two-stroke engines that require API TC and JASO FC performance levels.

### Specifications & Approvals

Mobil Extra 2T meets or exceeds the following industry specifications:	
API	TC
ISO	E-GC
JASO	FC
TISI	Meets

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit [www.exxonmobil.com](http://www.exxonmobil.com).

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.



## Typical Properties

Filling	RN 4603
<b>Mobil Extra 2T</b>	
Viscosity, ASTM D 445	
cSt @ 40°C	55
cSt @ 100°C	8.8
Viscosity Index, ASTM D 2270	135
Sulfated Ash, wt%, ASTM D 874	0.06
Pour Point, °C, ASTM D 97	-24
Flash Point, °C, ASTM D 92	110
Density @ 15°C kg/l, ASTM D 4052	0.867

## Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Extra 2T are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

