



Mobil Super 2T

High Performance Two-Stroke Engine Oil

Product Description

Mobil Super 2T is a high performance, two-stroke engine oil for use in motorcycles, snowmobiles and lean oil/fuel ratio chain saws.

Mobil Super 2T is pre-diluted to ensure rapid mixing when added to fuel.

Features & Benefits

Mobil Super 2T combines quality mineral oils with a superior additive system to provide good overall cleaning and performance. Key features and benefits include:

Features	Advantages and Potential Benefits
Good wear protection	Longer engine life
Thermal and oxidation stability and deposit control	Cleaner engines resulting in extended spark plug and valve life, reduced ring sticking and piston tightening as well as protection against pre-ignition problems
Good corrosion protection properties	Longer engine life
Reduces pre-ignition	Improved fuel efficiency and extended piston life

Applications

Mobil Super 2T is specifically recommended for lubrication of two-stroke engines where an API TC and JASO FB level performance is recommended.

Specifications & Approvals

Mobil Super 2T meets or exceeds the following industry specifications:	
API	TC
ISO	E-GB
JASO	FB

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.



Typical Properties

Filling	RN 4602
Mobil Super 2T	
Viscosity, ASTM D 445	
cSt @ 40°C	63
cSt @ 100°C	8.7
Viscosity Index, ASTM D 2270	110
Sulfated Ash, wt%, ASTM D 874	0.05
Pour Point, °C, ASTM D 97	-12
Flash Point, °C, ASTM D 92	132
Density @ 15°C kg/l, ASTM D 4052	0.878

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Special 2T are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

